


पथरी शनश्चरे नगरपालिका

नगर कार्यपालिकाको कार्यालय

पथरी मोरङ


डेरी सम्बन्धि उपकरणको बजार दररेट माग फारम (BOQ) आ.व. २०८२/०८३

S.N	NAME OF PARTICULAR	SPECIFICATION	UNIT	PRICE Per Unit in NPR	VAT IF INCLUSIVE
1	Chilling vat with storage tank 2000 liters	<ul style="list-style-type: none">• 2000 liters of chilling vat with storage tank.• Tank made fully stainless-steel inner tank of 2 mm and side cover of 1.5 mm, Puff insulation of 3 inch.• Inner m/s framing painted• Cooling Capacity Of 10500kcl/Hour or aprox 15000 watts• Material quality: Stainless-steel AISI 304 grades• Type Of Refrigerant Of R-134/404a• Maximum Cooling Time Of 3hr. 30mins• Temp Range Considered Of 35->4c• Power Requirement of Single Phase	tank		



R. S. D.

		<ul style="list-style-type: none"> • 3 Ton 2 compressor with copper pipe 0.5 inch. • Agitator 28-40rpm • Outlet Valve: 30-40mm • Condenser Air Cooled, Expansion valve • Filter dryer, liquid receiver. • Fully automatic digital control system with all complete electrical panel. • Installation and testing as per site engineer. • Warranty: 24 months 		
2	Chilling Vat with Storage tank 1000 liters	<ul style="list-style-type: none"> • 1000 liters of chilling vat with storage tank • Tank made fully stainless-steel inner tank of 2 mm and side cover of 1.5 mm, Puff insulation of 3 inch • Inner m/s framing painted • Cooling Capacity Of 5600kc/ Hour or aprox 7500 watts • Material quality: Stainless-steel AISI 304 grades • Type Of Refrigerant Of R-134/404a • Maximum Cooling Time Of 3hr. 30mins • Temp Range Considered Of 35->4c 		



[Handwritten Signature]

		<ul style="list-style-type: none">• Power Requirement of Single Phase• 2 Ton Single compressor with copper pipe 0.5 inch.• Agitator 28-40rpm• Outlet Valve: 30-40mm• Condenser Air Cooled, Expansion valve, • Filter dryer, liquid receiver.• Fully automatic digital control system with all complete electrical panel.• Installation and testing as per site engineer.• Warranty: 24 months	